

# K4GFGP1022N

GAS FRYER DOUBLE TANK 22+22 LT. - PERFORMANCE LINE



## PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Oil heating achieved through **optimized combustion stainless steel burners** equipped with a heat exchanger in the tank. Powerful and quick intervention of the heating elements to prevent the temperature from dropping when the product is poured into the tank.

**Two tanks of 22 liters each**, equipped with electromechanical valve for gas control and electric working thermostat with regulation **between 90°C and 190°C**. Safety guaranteed by a thermocouple kept active by the pilot burner flame. Additional safety thermostat. Stainless steel tanks with rounded edges sloping towards the drain hole connected to a stainless steel container to collect the oil. Oil drains from the tank via a tap into an internal collection container with a filter.

**Standard provided** with steel baskets coated with a layer of protective material and stainless steel basin cover.

**Standard provided** with one stainless steel oil container with filter.

Moulded AISI 304 stainless steel worktop for easy cleaning. Front panel in AISI 304 stainless steel. Cold-formed stainless steel tanks.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Tested with natural gas or LPG, according to the user's needs.

**Height-adjustable** stainless steel legs.

Accessories available **on demand**.



## TECHNICAL SPECIFICATIONS

**Width:** 800 mm  
**Depth:** 900 mm  
**Height:** 850 mm  
**Weight:** 107 kg  
**Volume:** 0.99 m<sup>3</sup>  
**Electrical power:** 0.02 kW  
**Gas power:** 42.00 kW

