

# Polar — PO 5T PL

## Catering



### Technical data

Gross volume	159 lt
Working temperature	-40+10 °C
Performance from +90°C to +3°C	20 Kg
Performance from +90°C to -18°C	14 Kg
Motor type	Plug-in
Refrigerant	R452A
Refrigeration power	1748 W (-10°C / +40°C)
Absorption	1180 W
Voltage/Frequency	230V/1~/50Hz

### Refrigeration details

Refrigeration unit	Tropicalized condensing unit. Equipped with thermostatic valve. Condenser is oversized to ensure maximum efficiency and performance
Refrigerant charge	900 gr
Evaporator	Conceived to provide the maximum exchange surface and to ensure optimal performance. Equipped with cataphoresis anti-corrosion treatment and door that can be opened for an easy cleaning
Defrost	Manual by air. The equipment can work for 24 hours avoiding ice formation on the evaporator
Condensate evaporation	Through easy extractable condensation collector tray (for installations without water drain system)

## Construction details

---

Product dimensions WxDxH	800x700x850
Packaging dimensions WxDxH	870x770x990
Gross weight	111 Kg
Worktop	Stainless steel AISI 304 worktop (4 cm thickness) reinforced to carry up the weight of an oven
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; motor unit compartment and bottom in colaminated steel
Insulation thickness	60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Door	1 Self-closing door right hinged, not reversible on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (45mm-60mm)

## Functions

---

Control panel	Capacitive, simple and intuitive display
Open door alarm	Visual and acoustic
Functions	Soft and hard blast chilling, soft and hard blast freezing, automatic end cycle holding, pre-cooling
Probe	Needle probe with automatic recognition of the probe inserted in the food

## Accessories

---

No. included accessories	5 - Pair of runners for GN 1/1 and EN 600x400 mm
--------------------------	--

## Versions

---

Versions	Water cooling unit/ Power supply frequency 60Hz
----------	---