

# Gastronorm — TG2 M PL TN

## Catering



### Technical data

Gross volume	281 lt
Working temperature	0+8 °C
Motor type	Plug-in
Refrigerant	R452A
Refrigeration power	377 W (-10°C / +45°C)
Absorption	377 W
Voltage/Frequency	230V/1~/50Hz

### Energy data (UE Reg. 2015/1094)

Net Volume	179 lt
Climate class	4 / (30°C 55%)

### Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit
Refrigerant charge	230 gr
Evaporator	With cataphoresis anti-corrosion treatment
Defrost	Automatic by air
Condensate evaporation	Automatic through anti-corrosion treated compressor coil

## Construction details

---

Product dimensions WxDxH	1368x700x850
Packaging dimensions WxDxH	1435x750x980
Gross weight	109 Kg
Worktop	Sturdy and resistant stainless steel AISI 304 worktop with rounded edges
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	50 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	2 Self-closing doors with 120° door stop, reversibles on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)

## Functions

---

Control panel	Compact, simple and intuitive touch screen display. Tilted control panel
---------------	--

## Accessories

---

No. included accessories	2 - Plastic-coated grid GN 1/1 530x325 mm 2 - Pair of runners for grid 530x325 mm
--------------------------	--

## Versions

---

Versions	Power supply frequency 60Hz
----------	-----------------------------