

Gastronorm — TG3 M PL TN

Catering



Technical data

Gross volume	424 lt
Working temperature	0+8 °C
Motor type	Plug-in
Refrigerant	R452A
Refrigeration power	377 W (-10°C / +45°C)
Absorption	377 W
Voltage/Frequency	230V/1~/50Hz

Energy data (UE Reg. 2015/1094)

Net Volume	261 lt
Climate class	4 / (30°C 55%)

Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit
Refrigerant charge	230 gr
Evaporator	With cataphoresis anti-corrosion treatment
Defrost	Automatic by air
Condensate evaporation	Automatic through anti-corrosion treated compressor coil

Construction details

Product dimensions WxDxH	1822x700x850
Packaging dimensions WxDxH	1890x750x980
Gross weight	144 Kg
Worktop	Sturdy and resistant stainless steel AISI 304 worktop with rounded edges
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel
Insulation thickness	50 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)
Inner corners	Rounded for an easy cleaning
Door	3 Self-closing doors with 120° door stop, reversibles on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)

Functions

Control panel	Compact, simple and intuitive touch screen display. Tilted control panel
---------------	--

Accessories

No. included accessories	3 - Plastic-coated grid GN 1/1 530x325 mm 3 - Pair of runners for grid 530x325 mm
--------------------------	--

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------